

Road Blocker



JSLZ1204-01 3130x2100x953
JSLZ1205-01 3430x2100x953

Model No.	JSLZ1204-01/1205--01
Specification	1. Carrying capacity: ≤80 tons 2. Voltage: 380V or 220V (for option) 3. Communication Interface: Standard RS485; Communication Range ≤1200M 4. Barrier opening time: ≤5S passing allowed, closing time: ≤4.5S passing forbidden 5. Hydraulic oil type: 45#hydraulic oil 6. Working Environment Temperature:-20℃—+50℃ had updated to -20℃—65, the colour of appearance is optional
Features	1. System can interface with PLC Controller 2. The motor will stop running after working 5 minutes without load until new instruction received. 3. Removable structure to facilitate installation and maintenance 4. In case of power failure, the barrier can be manually operated to the horizontal position. 5. With temperature surveillance and automatic compensation function which can ensure system works normally even in low temperature. 6. With infrared protection function to prevent the barrier rising in the event of wrong activation when there is objects on it (optional) With copy function for instructions and systems parameter to obtain correct operation (optional)
Remarks	The vehicle blocker is an equipment to control the passing of vehicle, It can be used with barrier gate system, also can use independently, mainly used for road control at customs, border inspection, Government vital installations, Airport, Jail, wharf, Logistics military base, nuclear power station and other special places.



JIESHUN
TECHNOLOGY
SINGAPORE